

## **PART 1 - GENERAL**

### **1.1 SUMMARY**

- A. Section Includes:
  - 1. Packaged, air-cooled chillers.

### **1.2 DEFINITIONS**

- A. BAS: Building automation system.
- B. COP: Coefficient of performance. The ratio of the rate of heat removal to the rate of energy input using consistent units for any given set of rating conditions.
- C. EER: Energy-efficiency ratio. The ratio of the cooling capacity given in terms of Btu/h to the total power input given in terms of watts at any given set of rating conditions.
- D. IPLV: Integrated part-load value. A single-number part-load efficiency figure of merit calculated per the method defined by ARI 506/110 and referenced to ARI standard rating conditions.
- E. kW/Ton: The ratio of total power input of the chiller in kilowatts to the net refrigerating capacity in tons at any given set of rating conditions.
- F. NPLV: Nonstandard part-load value. A single-number part-load efficiency figure of merit calculated per the method defined by ARI 506/110 and intended for operating conditions other than ARI standard rating conditions.

### **1.3 PERFORMANCE REQUIREMENTS**

- A. Site Altitude: Chiller shall be suitable for altitude in which installed without affecting performance indicated. Make adjustments to affected chiller components to account for site altitude.

### **1.4 ACTION SUBMITTALS**

- A. Product Data: For each type of product indicated. Include refrigerant, rated capacities, operating characteristics, furnished specialties, and accessories.
  - 1. Performance at ARI standard conditions and at conditions indicated.
  - 2. Performance at ARI standard unloading conditions.
  - 3. Minimum evaporator flow rate.
  - 4. Refrigerant capacity of chiller.
  - 5. Oil capacity of chiller.

## 15626 ROTARY-SCREW WATER CHILLERS

6. Fluid capacity of evaporator.
  7. Characteristics of safety relief valves.
  8. Minimum entering condenser-air temperature.
  9. Maximum entering condenser-air temperature.
  10. Performance at varying capacities with constant-design entering condenser-air temperature. Repeat performance at varying capacities for different entering condenser-air temperatures from design to minimum in 10 deg F increments.
- B. Shop Drawings: Include plans, elevations, sections, details, and attachments to other work.
1. Detail equipment assemblies and indicate dimensions, weights, load distribution, required clearances, method of field assembly, components, and location and size of each field connection.
  2. Wiring Diagrams: For power, signal, and control wiring.

### **1.5 INFORMATIONAL SUBMITTALS**

- A. Certificates: For certification required in "Quality Assurance" Article.
- B. Startup service reports.
- C. Warranty: Sample of special warranty.

### **1.6 CLOSEOUT SUBMITTALS**

- A. Operation and Maintenance Data: For each chiller to include in emergency, operation, and maintenance manuals.

### **1.7 QUALITY ASSURANCE**

- A. ARI Certification: Certify chiller according to ARI 590 certification program(s).
- B. ARI Rating: Rate chiller performance according to requirements in ARI 506/110.
- C. ASHRAE Compliance:
  1. ASHRAE 15 for safety code for mechanical refrigeration.
  2. ASHRAE 147 for refrigerant leaks, recovery, and handling and storage requirements.
- D. ASME Compliance: Fabricate and label chiller to comply with ASME Boiler and Pressure Vessel Code: Section VIII, Division 1, and include an ASME U-stamp and nameplate certifying compliance.
- E. Comply with NFPA 70.

## 15626 ROTARY-SCREW WATER CHILLERS

- F. Comply with requirements of UL and UL Canada and include label by a qualified testing agency showing compliance.

### **1.8 DELIVERY, STORAGE, AND HANDLING**

- A. Ship chiller with a full charge of refrigerant. Charge chiller with nitrogen if refrigerant is shipped in containers separate from chiller.
- B. Ship each oil-lubricated chiller with a full charge of oil.

### **1.9 COORDINATION**

- A. Coordinate size and location of existing concrete base and surrounding fence enclosure with actual equipment provided. If existing base/fence enclosure is not large enough for chiller include provisions to enlarge as required.

### **1.10 WARRANTY**

- A. Special Warranty: Manufacturer's standard form in which manufacturer agrees to repair or replace components of chillers that fail in materials or workmanship within specified warranty period.
  - 1. Extended warranties include, but are not limited to, the following:
    - a. Complete chiller including refrigerant and oil charge.
    - b. Parts and labor.
    - c. Loss of refrigerant charge for any reason.
    - d. Full parts/labor Warranty Period: Two years from date of Substantial Completion.
    - e. Compressor only warranty: parts only for 5 years from date of Substantial Completion.

## **PART 2 - PRODUCTS**

### **2.1 PACKAGED, AIR-COOLED CHILLERS**

- A. Basis-of-Design Product: Subject to compliance with requirements, provide product indicated on Drawings or comparable product by one of the following:
  - 1. McQuay International.
  - 2. Trane.
  - 3. York International Corporation.

## 15626 ROTARY-SCREW WATER CHILLERS

- B. Description: Factory-assembled and run-tested chiller complete with base and frame, condenser casing, compressors, compressor motors and motor controllers, evaporator, condenser coils, condenser fans and motors, electrical power, controls, and accessories.
- C. Cabinet:
  - 1. Base: Galvanized-steel base extending the perimeter of chiller. Secure frame, compressors, and evaporator to base to provide a single-piece unit.
  - 2. Frame: Rigid galvanized-steel frame secured to base and designed to support cabinet, condenser, control panel, and other chiller components not directly supported by base.
  - 3. Casing: Galvanized steel.
  - 4. Finish: Coat base, frame, and casing with a corrosion-resistant coating capable of withstanding a 500-hour salt-spray test according to ASTM B 117.
  - 5. Sound-reduction package designed to reduce sound level without affecting performance to level indicated on schedule.
- D. Compressors:
  - 1. Description: Positive displacement hermetically sealed.
  - 2. Casing: Cast iron, precision machined for minimum clearance about periphery of rotors.
  - 3. Rotors: Manufacturer's standard one- or two-rotor design.
  - 4. Each compressor provided with suction and discharge shutoff valves, crankcase oil heater, and suction strainer.
- E. Service: Easily accessible for inspection and service.
- F. Capacity Control: On-off compressor cycling and modulating slide-valve assembly or port unloaders combined with hot-gas bypass, if necessary, to achieve performance indicated.
  - 1. Maintain stable operation throughout range of operation. Configure to achieve most energy-efficient operation possible.
  - 2. Operating Range: From 100 to 15 percent of design capacity without using hot gas bypass.
  - 3. Condenser-Air Unloading Requirements over Operating Range: Constant-design entering condenser-air temperature.
  - 4. For units equipped with a variable frequency controller, capacity control shall be both "valveless" and "stepless," requiring no slide valve or capacity-control valve(s) to operate at reduced capacity.
- G. Oil Lubrication System: Consisting of pump if required, filtration, heater, cooler, factory-wired power connection, and controls.
  - 1. Provide lubrication to bearings, gears, and other rotating surfaces at all operating, startup, shutdown, and standby conditions including power failure.

## 15626 ROTARY-SCREW WATER CHILLERS

2. Thermostatically controlled oil heater properly sized to remove refrigerant from oil.
3. Factory-installed and pressure-tested piping with isolation valves and accessories.
4. Oil compatible with refrigerant and chiller components.
5. Positive visual indication of oil level.

### H. Vibration Control:

1. Vibration Balance: Balance chiller compressors and drive assemblies to provide a precision balance that is free of noticeable vibration over the entire operating range.
  - a. Overspeed Test: 25 percent above design operating speed.
2. Isolation: Mount individual compressors on vibration isolators.

### I. Compressor Motors:

1. Hermetically sealed and cooled by refrigerant suction gas.
2. High-torque, induction type with inherent thermal-overload protection on each phase.

### J. Compressor Motor Controllers:

1. Across the Line: NEMA ICS 2, Class A, full voltage, nonreversing, or solid state.
2. Star-Delta, Reduced-Voltage Controller: NEMA ICS 2, closed transition, or solid state.
3. Variable Frequency Controller (if applicable):
  - a. Motor controller shall be factory mounted and wired on the chiller to provide a single-point, field-power termination to the chiller and its auxiliaries.
  - b. Description: NEMA ICS 2; listed and labeled as a complete unit and arranged to provide variable speed by adjusting output voltage and frequency.
  - c. Enclosure: Unit mounted, NEMA 250, Type 3R, with hinged full-front access door with lock and key.
  - d. Integral Disconnecting Means: Door-interlocked, NEMA AB 1, instantaneous-trip circuit breaker with lockable handle. Minimum withstand rating shall be as required by electrical power distribution system, but not less than 42,000 A.
  - e. Technology: Pulse width modulated (PWM) output suitable for constant or variable torque loads.
  - f. Motor current at start shall not exceed the rated load amperes, providing no electrical inrush.

### K. Refrigerant Circuits:

1. Refrigerant Type: R-134a or any HFC. Classified as Safety Group A1 according to ASHRAE 34.

## 15626 ROTARY-SCREW WATER CHILLERS

2. Refrigerant Compatibility: Chiller parts exposed to refrigerants shall be fully compatible with refrigerants, and pressure components shall be rated for refrigerant pressures.
3. Refrigerant Circuit: Each shall include a thermal- or electronic-expansion valve, refrigerant charging connections, a hot-gas muffler, compressor suction and discharge shutoff valves, a liquid-line shutoff valve, a replaceable-core filter-dryer, a sight glass with moisture indicator, a liquid-line solenoid valve, and an insulated suction line.
4. Pressure Relief Device:
  - a. Comply with requirements in ASHRAE 15 and in applicable portions of ASME Boiler and Pressure Vessel Code: Section VIII, Division 1.
  - b. ASME-rated, spring-loaded pressure relief valve; single- or multiple-reseating type.

### L. Evaporator:

1. Description: Shell-and-tube design.
  - a. Direct-expansion (DX) type with fluid flowing through the shell, and refrigerant flowing through the tubes within the shell.
  - b. Flooded type with fluid flowing through tubes and refrigerant flowing around tubes within the shell.
2. Code Compliance: Tested and stamped according to ASME Boiler and Pressure Vessel Code: Section VIII, Division 1.
3. Shell Material: Carbon steel.
4. Shell Heads: Removable carbon-steel heads located at each end of the tube bundle.
5. Fluid Nozzles: Terminated with mechanical-coupling (grooved) end connections for connection to field piping.
6. Tube Construction: Individually replaceable copper tubes with enhanced fin design, expanded into tube sheets.
7. Heater: Factory-installed and -wired electric heater with integral controls designed to protect the evaporator to minus 20 deg F.

### M. Air-Cooled Condenser:

1. Plate-fin coil with integral subcooling on each circuit, rated at 450 psig.
  - a. Construct coil casing of galvanized or stainless steel.
  - b. Construct coils of copper tubes mechanically bonded to aluminum fins.
  - c. Coat coils with a baked-epoxy, corrosion-resistant coating after fabrication.
  - d. Hail Protection: Provide condenser coils with louvers, baffles, or hoods to protect against hail damage.

## 15626 ROTARY-SCREW WATER CHILLERS

2. Fans: Direct-drive propeller type with statically and dynamically balanced fan blades, arranged for vertical air discharge.
3. Fan Motors: Totally enclosed nonventilating (TENV) or totally enclosed air over (TEAO) enclosure, with permanently lubricated bearings. Equip each motor with overload protection integral to either the motor or chiller controls.
4. Fan Guards: Steel safety guards with corrosion-resistant coating.

### N. Electrical Power:

1. Factory-installed and -wired switches, motor controllers, transformers, and other electrical devices necessary shall provide a single-point, field-power connection to chiller.
2. House in a unit-mounted, NEMA 250, Type 3R enclosure with hinged access door with lock and key or padlock and key.
3. Wiring shall be numbered and color-coded to match wiring diagram.
4. Install factory wiring outside of an enclosure in a raceway.
5. Field-power interface shall be to NEMA KS 1, heavy-duty, nonfused disconnect switch.
6. Provide branch power circuit to each motor and to controls with one of the following disconnecting means:
  - a. NEMA KS 1, heavy-duty, fusible switch with rejection-type fuse clips rated for fuses. Select and size fuses to provide Type 2 protection according to IEC 60947-4-1.
  - b. NEMA AB 1, motor-circuit protector (circuit breaker) with field-adjustable, short-circuit-trip set point.
7. Provide each motor with overcurrent protection.
8. Overload relay sized according to UL 1995 or an integral component of chiller control microprocessor.
9. Phase-Failure and Undervoltage Relays: Solid-state sensing with adjustable settings.
10. Provide power factor correction capacitors to correct power factor to 0.90 at full load.
11. Control Transformer: Unit-mounted transformer with primary and secondary fuses and sized with enough capacity to operate electrical load plus spare capacity.
  - a. Power unit-mounted controls where indicated.
12. Control Relays: Auxiliary and adjustable time-delay relays.
13. For chiller electrical power supply, indicate the following:
  - a. Current and phase to phase for all three phases.

## 15626 ROTARY-SCREW WATER CHILLERS

- b. Voltage, phase to phase, and phase to neutral for all three phases.
  - c. Three-phase real power (kilowatts).
  - d. Three-phase reactive power (kilovolt amperes reactive).
  - e. Power factor.
  - f. Running log of total power versus time (kilowatt-hours).
  - g. Fault log, with time and date of each.
- O. Controls:
- 1. Standalone and microprocessor based.
  - 2. Enclosure: Share enclosure with electrical power devices or provide a separate enclosure.
  - 3. Operator Interface: Multiple-character digital or graphic display with dynamic update of information and with keypad or touch-sensitive display located on front of control enclosure. In either imperial or metric units, display the following information:
    - a. Date and time.
    - b. Operating or alarm status.
    - c. Operating hours.
    - d. Outdoor-air temperature if required for chilled-water reset.
    - e. Temperature and pressure of operating set points.
    - f. Entering and leaving temperatures of chilled water.
    - g. Refrigerant pressures in evaporator and condenser.
    - h. Saturation temperature in evaporator and condenser.
    - i. No cooling load condition.
    - j. Elapsed time meter (compressor run status).
    - k. Antirecycling timer status.
    - l. Percent of maximum motor amperage.
    - m. Current-limit set point.
    - n. Number of compressor starts.
  - 4. Control Functions:
    - a. Manual or automatic startup and shutdown time schedule.
    - b. Entering and leaving chilled-water temperatures, control set points, and motor load limits. Chilled-water leaving temperature shall be reset by existing DDC system.



## 15626 ROTARY-SCREW WATER CHILLERS

- c. Current limit and demand limit.
  - d. External chiller emergency stop.
  - e. Antirecycling timer.
  - f. Automatic lead-lag switching.
  - g. Thermal storage.
5. Manually Reset Safety Controls: The following conditions shall shut down chiller and require manual reset:
- a. Low evaporator pressure or high condenser pressure.
  - b. Low chilled-water temperature.
  - c. Refrigerant high pressure.
  - d. High or low oil pressure.
  - e. High oil temperature.
  - f. Loss of chilled-water flow.
  - g. Control device failure.
6. Trending: Capability to trend analog data of up to five parameters simultaneously over an adjustable period and frequency of polling.
7. Security Access: Provide electronic security access to controls through identification and password with at least three levels of access: view only; view and operate; and view, operate, and service.
8. Control Authority: At least four conditions: Off, local manual control at chiller, local automatic control at chiller, and automatic control through a remote source.
9. BAS Interface: Factory-installed hardware and software to enable the BAS to monitor, control, and display chiller status and alarms.
- a. Hardwired Points (contractor option for BACnet interface):
    - 1) Monitoring: On-off status, common trouble alarm.
    - 2) Control: On-off operation.
    - 3) CWS set point adjustment
- P. Insulation:
- 1. Material: Closed-cell, flexible elastomeric, thermal insulation complying with ASTM C 534, Type I for tubular materials and Type II for sheet materials.
  - 2. Thickness: 3/4 inch.

## 15626 ROTARY-SCREW WATER CHILLERS

3. Factory-applied insulation over cold surfaces of chiller components.
  - a. Adhesive: As recommended by insulation manufacturer and applied to 100 percent of insulation contact surface. Seal seams and joints.
4. Apply protective coating to exposed surfaces of insulation to protect insulation from weather.

### Q. Accessories:

1. Factory-furnished, chilled-water flow switches for field installation.
2. Individual compressor suction and discharge pressure gages with shutoff valves for each refrigerant circuit.

### R. Capacities and Characteristics: Refer to schedule on drawings.

## 2.2 SOURCE QUALITY CONTROL

- A. Perform functional tests of chillers before shipping.
- B. Factory run test each air-cooled chiller with water flowing through evaporator.
- C. Factory test and inspect evaporator according to ASME Boiler and Pressure Vessel Code: Section VIII, Division 1.
- D. For chillers located outdoors, rate sound power level according to ARI 370.

## PART 3 - EXECUTION

### 3.1 EXAMINATION

- A. Examine chillers before installation. Reject chillers that are damaged.
- B. Examine roughing-in for equipment support, anchor-bolt sizes and locations, piping, and electrical connections to verify actual locations, sizes, and other conditions affecting chiller performance, maintenance, and operations before equipment installation.
  1. Final chiller locations indicated on Drawings are approximate. Determine exact locations before roughing-in for piping and electrical connections.
- C. Proceed with installation only after unsatisfactory conditions have been corrected.

### 3.2 CHILLER INSTALLATION

- A. Equipment Mounting:
  1. Install chiller on existing concrete pad.
- B. Maintain manufacturer's recommended clearances for service and maintenance.

- C. Charge chiller with refrigerant and fill with oil if not factory installed.
- D. Install separate devices furnished by manufacturer and not factory installed.

### **3.3 CONNECTIONS**

- A. Comply with requirements for piping specified in Section 15181 "Hydronic Piping," Section 15179 "Hydronic Piping Specialties". Drawings indicate general arrangement of piping, fittings, and specialties.
- B. Install piping adjacent to chiller to allow service and maintenance.
- C. Evaporator Fluid Connections: Connect to evaporator inlet with shutoff valve, flexible connector, thermometer, and plugged tee with pressure gage. Connect to evaporator outlet with shutoff valve, balancing valve, flexible connector, flow switch, thermometer, plugged tee with shutoff valve and pressure gage, and drain connection with valve. Make connections to chiller with a mechanical coupling.
- D. Connect each chiller drain connection with a union and drain pipe, and extend pipe, full size of connection, to floor drain. Provide a shutoff valve at each connection.

### **3.4 STARTUP SERVICE**

- A. Engage a factory-authorized service representative to perform startup service.
  - 1. Complete installation and startup checks according to manufacturer's written instructions.
  - 2. Verify that refrigerant charge is sufficient and chiller has been leak tested.
  - 3. Verify that pumps are installed and functional.
  - 4. Verify that thermometers and gages are installed.
  - 5. Operate chiller for run-in period.
  - 6. Check bearing lubrication and oil levels.
  - 7. For chillers installed indoors, verify that refrigerant pressure relief device is vented outdoors.
  - 8. Verify proper motor rotation.
  - 9. Verify static deflection of vibration isolators, including deflection during chiller startup and shutdown.
  - 10. Verify and record performance of fluid flow and low-temperature interlocks for evaporator.
  - 11. Verify and record performance of chiller protection devices.
  - 12. Test and adjust controls and safeties. Replace damaged or malfunctioning controls and equipment.

## 15626 ROTARY-SCREW WATER CHILLERS

- B. Inspect field-assembled components, equipment installation, and piping and electrical connections for proper assembly, installation, and connection.
- C. Prepare test and inspection startup reports.

### **3.5 DEMONSTRATION**

**END OF SECTION**